



A X E Z E

control.track.secure

AR-S-W Standalone RID access control system

AR-S- W2-EM

- Waterproof Standalone Prox Card Reader w remote for programming
- Anti-Tamper fitted
- Programming card to Add and Remove Cards

AR-S-W2-A Weatherproof Reader (EM+HID)

- RFID card reader
- Waterproof, rated to IP68
- User capacity: 10,000
- Card Interface: 125KHz EM +/-or HID card
- Remote control for programming
- Wiegand 26 input/output
- Block enrolment

AR-S-W2-A works with your electric door strike.

- If the door strike is already fitted you can easily install this unit yourself.
- If you need to purchase a door strike, all Security companies and Bunnings sell them and you can install it yourself.
- If you are not a home handyman you can arrange for an electrician, carpenter, security installer to install the system for you.

Additional cards and keyfobs available from Axeze



Appearance: plastic matte technic, durable.

Support Card: 125KHz EM, 125KHz HID, 13.56MHz.

Output Format: 26bit is factory default setting.

For Wiegand 26, reader will output according to card's format automatically.

Ultra-low Power Consumption: $\leq 30\text{mA}$.

Built-in optical tamper alarm technology.

Protective Performance: IP65 (fully-potted), tamper alarm.

Certificate: CE

Standalone Reader and Controller and Slave Readers

Specifications

Supply Voltage: 12VDC

Standby Current: $\leq 30\text{mA}$

Communication Interface: Wiegand26-37

Response Time: 0.1s

Card Reading Range: 3-6cm/2-6cm

Operating Temperature: $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$

Humidity: 0-95%

Level of Protection: IP65

Antistatic: 15KV

Transmit Distance: 100M

Cable Length: 90-100cm

Dimension: 103mm \times W48mm \times H23mm



Anti-tamper Technology

Built-in light dependent resistor (LDR) for anti-tamper. It will alarm once there is a person unauthorized try to access.